

S9700-23D

Disaggregated Core/Edge Router



The S9700-23D is the best of breed robust, flexible and carrier-grade disaggregated IP/MPLS router that can be deployed in the core or edge to transport services over a scalable next-gen service provider network. Equipped with 400GE service and fabric ports, S9700-23D enables fault & performance monitoring, non-stop routing support for control and data plane, and comprehensive high-availability networks.

The S9700-23D can be positioned as standalone or coupled with fabric router in small, medium and large clusters enabling 4Tb to 192Tb maximum switching capacity. By connecting to S9705-48D (Fabric), it scales out not only economically & rapidly, but brings down also the total cost of ownership.

S9700-23D adopts the innovative discrete NCP (Network Cloud Processor) and NCF (Network Cloud Fabric) building blocks providing flexibility to core router needs in the industry, integral to Ethernet switching performance and intelligence to networks while minimizing the network complexity.

Key Benefits

- ▶ Accelerated table lookup, packet buffering, and control memory with low latency high bandwidth memory
- ▶ Flexible and programmable packets processor
- ▶ Individual BMC operation
- ▶ High density ports with low power consumption
- ▶ Transparent networking, interoperability with S9705-48D
- ▶ Upstream connectivity management supported by three flexibly configured fabric pipes
- ▶ Dynamic distribution and routing through automatic fault detection and recovery

Key Features

- ▶ 10 x 400GE QSFP-DD service ports
- ▶ 13 x 400GE QSFP-DD fabric ports
- ▶ Service Ports support 4x100GE break-out
- ▶ 1 + 1 hot swappable PSU FRU
- ▶ 3 + 1 hot swappable Fan FRU
- ▶ Micro USB and RJ-45 console port
- ▶ 8GB deep buffering and Intel Broadwell-DE 8 core at 2 GHz
- ▶ 64GB memory DDR4 RDIMM with ECC



Specifications

Physical

- 10 x 400GE QSFP-DD service ports
- 13 x 400GE QSFP-DD fabric ports
- 1 x RJ-45 + Micro USB serial console ports
- 1 x 1GBase-T Ethernet port for Out-of-Band management
- 1 x USB 2.0 Type-A general purpose port
- 2 x 10GBase-X SFP+ management ports

Processor Intel® Broadwell-DE 8 core @ 2.0 GHZ

Memory 2 x 32GB DDR4 RDIMM with ECC support

Storage 2 x M.2 SATA SSD 128GB

ASIC Broadcom BCM88690

LED

- 2 x power status
- Fan status
- System status
- Per port link status
- Beacon
- Per fan status
- Per PSU status

Chassis (WxDxH) 2RU, 436 x 762 x 87.6 mm | 17.17 x 30 x 3.45 in.
Weight: 23.9 kg (52.8 lbs)

Fan Trays Hot swappable, 3+1 redundant FRU

Environmental

Power supply Hot swappable, 1+1 redundant FRU
AC input: 200 ~ 240V, 12.5A, 50 ~ 60Hz
DC input: -40 ~ -72V, 60 ~ 33A
Max power: 2000 Watts

Operating Specs. Operating temperature: 0°C to 45°C (32°F to 113°F)
Operating humidity: 5% to 85% (RH), noncondensing
Altitude: 1,829 m (6,000 ft.)

Non-Operating Specs. Storage temperature: -40°C to 70°C (-40°F to 158°F)
Storage humidity: 5% to 95% (RH), non-condensing

Performance

Switching Capacity 4.8 Tbps

Packet Throughput 2000 Mpps

Regulatory Compliance

Safety NEBS Level3
UL 62368-1
IEC/EN 60950-1
IEC/EN 62368-1
BSMI CNS 14336-1

EMC NEBS Level 3
FCC Part 15, Subpart B,
Class A EN55032, Class A
EN300 386
EN55024
EN55035
BSMI (CNS 13438), Class A

All product specifications are subject to change without notice



S9700-23D Views



Supported Accessories

Transceiver

400GE QSFP-DD SR8, 400GE QSFP-DD LR8, 400GE QSFP-DD DR4, 400GE QSFP-DD FR4,
100GE QSFP28 SR4, 100GE QSFP28 LR4, 100GE QSFP28 ER4

Cable types

400GE QSFP-DD DAC (Direct Attach Cable)
400GE QSFP-DD ACC (Active Copper Cable)
400GE QSFP-DD AOC (Active Optical Cable)
100GE QSFP28 DAC (Direct Attach Cable)
100GE QSFP28 ACC (Active Copper Cable)
100GE QSFP28 AOC (Active Optical Cable)

Power supply types

PSU-202-DESR 2000W DC, exhaust air, slim type, colored latch
PSU-202-AESR 2000W AC, exhaust air, slim type, colored latch

Fan types

FAN-803816-HC, exhaust air flow

Rack mounting kit

R19-970000-2630 adjustable mounting rail for 19" rack supporting depth from 26" to 30"