

Relion 1930g

Versatile Compute and Deep Learning Inference Server with M4 GPU Compatibility

OPEN SOLUTIONS

COMPUTE

STORAGE

NETWORK

CLOUD



Penguin Computing's Tundra OpenHPC platform delivers density, performance and serviceability for demanding customers. Tundra OpenHPC systems are optimized for CAPEX and OPEX in medium to large scale Data Centers.

With support for NVIDIA®'s hyperscale GPU accelerator, the Tesla® M4, and up to 1TB of RAM, the Relion 1930g is designed to provide data centers with breakthrough performance in a high density 10U form factor.

Based on Open Compute (OCP) Open Rack specification, Tundra OpenHPC reduces infrastructure costs over multiple technology generations. Due to the OCP Open Rack infrastructure's efficient use of available space, Penguin's Tundra ES solution can pack 3 Tundra Relion 1930g nodes per each horizontal rack unit. This allows up to 96 nodes per rack with the associated shared power infrastructure and fabric / networking switches.

Penguin Computing specializes in delivering turnkey High Performance Computing clusters and Data Center systems that include software solutions for cluster and workload management, high performance interconnects, storage systems and a power delivery infrastructure. All components are integrated in rack enclosures, configured for optimal performance by Penguin's HPC experts and ready to use.

Penguin systems are tested for compatibility with all major commercial and freely available Linux distributions and are available with Red Hat Enterprise Linux, SuSE Linux Enterprise Server or CentOS pre-installed.





Relion 1930g

Relion 1930g

- OCP OpenRack form factor, 1 OU, 3 Servers per Shelf
- Dual Socket Intel® Xeon E5-2600 v3 and v4 series
- Up to 384GB DDR4-2400MHz (6x DIMMs)
- Intel[®] C610 Chipset (Wellsburg)
- 2x GigE/RJ45 (Intel®I Springville)
- 1x Dedicated BMC
- 1x PCle x16 Gen3
- 1x PCle x8 Mezzanine Card
- Up to 2x 2.5" SATA SSDs
- Up to 4x M.2 NVMe (via PCle Mezz)

Dimensions

- 1.65" x 6.93" x 31.32"(H x W x D)
- Weight: 12.5 lbs.



OTHER TUNDRA ES PRODUCTS:





Relion X1904GT

- 1 OpenU Form Factor
- Dual Intel® Xeon ® E5-2600 v4 processors
- Up to 1TB DDR4-2400MHz (16x DIMMs)
- · Intel® C612 Chipset
- 2x PCle 3.0 (Speed depends on topology)
- 4x 2.5" SATA SSD
- Dual GbE LOM
- Dedicated BMC Port
- Support Asetek Direct-to-Chip Cool ing (CPUs and GPUs)
- Supports 4x GPGPU Nvidia Tesla P100, P100-SXM2, M40 and P40
- Flexible PCIe Topology

Relion Phi X1030e

- OCP OpenRack Form Factor
- · 10U, 3 Servers per Shelf
- Single Socket Intel® Xeon Phi TM 7200 Series, including -F (Omnipath)
- Up to 384GB DDR4-2400MHz (6x DIMMs)
- · Intel® C610 Chipset
- Shared BMC
- · 2x PCIe Gen3 x16 slots
- Up to 2x 2.5" SSD/U.2 NVMe
- Up to 8x M.2 NVMe Storage
- 2x 1GbE ports
- 1x mSATA (Onboard)
- Supports Intel® Omni-Path via KNL-F Processor or PCIe card.

Relion 1930e

- OCP OpenRack form factor, 1 OU, 3 Servers per Shelf
- Dual Socket Intel® E5-2600 v3/v4 Series
- Up to 1TB DDR4-2400MHz (16x DIMMs)
- Intel® C612 Chipset
- 2x GbE/RJ45 LOM
- 1x Dedicated BMC
- 1x PCle x16 Gen3 Slot
- 1x PCle x8 PCle Mezzanine Slot
- 1x 2.5" Fixed SATA SSD
- · Optional 1x FDR LOM
- Supports Asetek Direct-to-Chip Cooling

Valkre 1030c

- OCP OpenRack form factor, 1 OU, 3 Servers per Shelf
- Dual Cavium ThunderX Proessors based on ARM64 architechture
- Up to 1TB DDR4-2133MHz (16x DIMMs)
- 1x Dedicated BMC
- 2x 40GB Enternet interfaces
- 2x PCle 3.0 x16 LP card
- 1x 2.5" SATA/SSD HDDs

Penguin Computing specializes in delivering turn-key High Performance Computing clusters and Data Center systems that include software solutions for cluster and workload management, high performance interconnects, storage systems and a power delivery infrastructure. All components are integrated in rack enclosures, configured for optimal performance by Penguin's HPC experts and ready to use

Penguin systems are tested for compatibility with all major commercial and freely available Linux distributions and are available with Red Hat Enterprise Linux, SuSE Linux Enterprise Server or CentOS pre-installed.

FOR INFORMATION, PLEASE CONTACT:

sales@penguincomputing.com 1-888-PENGUIN (736-4846) twitter: @PenguinHPC

www.penguincomputing.com