

M3000-14XC Fronthaul Multiplexer

The UfiSpace M3000-14XC is a high-performance, versatile open networking fronthaul device that is designed to expand coverage and maximizes the DU resources with flexibility as service providers improve their services. It enables telecoms and service providers to optimize private 5G network by utilizing DU resources efficiently and to streamline upgrading process when service providers are increasing its service capacity.

The M3000-14XC is future-proofed with a powerful quad-core processor, a programmable FPGA, 14 high speed interfaces, and full timing features supporting IEEE 1588V2 and SyncE. It is suitable for both indoor and outdoor cabinet deployments with redundant, hot-swappable components for convenience, increased availability, reliability and lower costs of maintenance.



KEY BENEFITS

- Supports up to 64 RUs with cascading
- Extend service coverage and minimize DU resources needed by grouping RUs into one virtual cell.
- Future-proof for 5G with ultra-low forwarding latency, high precision frequency and phase timing synchronizations.
- Suitable for open fronthaul application and compliant to O-RAN standard.

KEY FEATURES

- Jumbo frame size up to 9000 bytes
- Cascade up to 8 FHMs
- Various fiber length delay compensation
- Configurable data compression mode
- Configurable IQ data width
- Configurable U/C plane VLAN ID
- CLI/SNMP/NETCONF management protocol
- Supports full SyncE and IEEE 1588V2 (T-GM**, T-BC**, and T-TC)
- Integrated Stratum 3E OCXO with Class C timing support Rich timing interfaces: ToD, 1PPS, BITS, 10MHz, and GNSS**

SPECIFICATIONS

PHYSICAL

- ◆ 8 x 10/25G SFP28 ports to O-RU
- ◆ 4 x 10/25G SFP28 ports to O-DU*
- ◆ 2 x 100G QSFP28 (Optional**)
- ◆ 1 x USB2.0 Type-A port
- ◆ 1 x RJ45 serial console port
- ◆ 2 x 100/1000M RJ45 management port

Processor	ARM Cortex-A53 4-Core 64-bit @ 1.0GHz
FPGA	Intel S10-TX(for O-RAN shared cell function)
Memory	4GB DDR4
Timing	1 x GNSS input SMA(**)
Interfaces	1 x 1PPS input/output SMB 1 x 10MHz input/output SMB 1 x BITS input/output RJ48 1 x ToD input/output RJ45
Hardware Timing Capabilities	Stratum 3E OCXO ITU-T Synchronous Ethernet (SyncE) IEEE 1588v2 (G.8275.1**, G.8275.2** PTS/APTS, T-TC, T-BC/OC**, T-GM**)
Chassis (WxDxH)	1 RU, 440 x 250 x 43.5 mm or 17.32" x 9.84" x 1.71" Net weight: 4.18 kg. or 9.21 lbs.
Redundancy	Hot swappable, 1+1 redundant PSUs
FAN	4 Fixed Fans

*Only port 8 is available to use for now, port 9-11 are reserved
**To be available with future premium version

ENVIRONMENTAL

Power Supply	AC input: 100 ~ 240V, 3A DC input: -36 ~ -75V, 8A Max power: 188 Watts
Max. Operating Specs.	Operating temperature: -40°C to 65°C (-40°F to 149°F) Operating humidity: 5% to 95% (RH), noncondensing
Max. Non-Operating Specs.	Storage temperature: -40°C to 70°C (-40°F to 158°F) Storage humidity: 5% to 93% (RH), non-condensing

PERFORMANCE

Coverage	Support up to 64 RUs by cascading 8 FHM's
----------	---

REGULATORY COMPLIANCE

Safety	UL 62368-1 IEC62368-1	EMC	FCC Part 15, Subpart B, Class A
--------	--------------------------	-----	---------------------------------

Specifications are subject to change without notice.

M3000-14XC

Telecom
Networking
Solutions

M3000-14XC Front and Back Views



SUPPORTED ACCESSORIES

Transceivers

25G SFP28 SR, 25G SFP28 LR, 25G SFP28 ER, 10G SFP+ SR, 10G SFP+ LR, 10G SFP+ ER

Cable Types

SMA coaxial cable with 1/4-36UNS-2B connector for GNSS
SMB coaxial cable with 10-32UNF-2A connector for 1PPS and 10MHz
Shield cable with RJ45 for ToD
Shield cable with RJ48 for BITS

Power Supply Types

PSU-201-DISB, 200W DC PSU, intake air flow
PSU-201-AISB, 200W AC PSU, intake air flow

